

EN 62479: 2010
EN 50663: 2017

TEST REPORT

FOR

Base station

Model No.: SID-ESL-19A, SID-ESL-0xA (x=1, 2, 3, 4, 6, ..., 100)

Trademark: N/A

Report No.: E01A23030814H00201

Issue Date: April 13, 2023

Prepared for

Guangdong SID Technology Co., Ltd.

**Room 101, Building 5, No. 21, Dongke Road, Dongcheng Street,
Dongguan City, Guangdong Province.**

Prepared by

**Dong Guan Anci Electronic Technology Co., Ltd.
1-2 Floor, Building A, No.11, Headquarters 2 Road, Songshan, Lake
Hi-tech Industrial Development Zone, Dongguan City, Guangdong Pr.,
China.**

**This report shall not be reproduced, except in full, without the written approval of
Dong Guan Anci Electronic Technology Co., Ltd.**

TABLE OF CONTENT

Description	Page
1. GENERAL INFORMATION	5
1.1 Description of Device (EUT).....	5
1.2 Test Facility.....	6
2. GENERAL PRODUCT INFORMATION	7
3. EN 62479 REQUIREMENT	8
3.1 General Description of Applied Standards.....	8
3.2 Human exposure to the Electromagnetic fields	8
3.3 RF Exposure Evaluation	8
4. APPENDIX PHOTOGRAPHS OF EUT	9

TEST REPORT DESCRIPTION

Applicant : Guangdong SID Technology Co., Ltd.
Room 101, Building 5, No. 21, Dongke Road, Dongcheng Street,
Dongguan City, Guangdong Province.
Guangdong SID Technology Co., Ltd.
Manufacturer : Room 101, Building 5, No. 21, Dongke Road, Dongcheng Street,
Dongguan City, Guangdong Province.
EUT : Base station
Model No. : SID-ESL-19A, SID-ESL-0xA (x=1, 2, 3, 4, 6, ..., 100)
Trade Mark : N/A
Input Rating : DC 12V, 1A from Adapter

Test Procedure Used:

EN 62479: 2010

EN 50663: 2017

The device described above is tested by Dong Guan Anci Electronic Technology Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report shows the EUT to be technically compliant with the EN 62479: 2010 and EN 50663: 2017 requirements. The test results are contained in this report and Dong Guan Anci Electronic Technology Co., Ltd. is assumed full responsibility for the accuracy and completeness of these tests.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Dong Guan Anci Electronic Technology Co., Ltd.

Date of Test :


March 29, 2023 to April 08, 2023

Prepared by :

Duke Liu / EMC Engineer

Approve & Authorized Signer :

Tiger Xu/EMC Supervisor



Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Version	/	E01A23030814H00201

1. GENERAL INFORMATION

1.1 Description of Device (EUT)

2.4G RFID	
Modulation:	GFSK
Operation frequency:	2400-2483.5MHz
Channel number:	40 channels
Antenna Gain:	0.5dBi
RF Power	1.33dBm

2.4G WIFI	
Modulation:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Operation frequency:	2412-2472 MHz
Channel number:	13 Channels for 802.11b; 13 Channels for 802.11g; 13 Channels for 802.11n(HT20); 13 Channels for 802.11n(HT40);
Antenna Gain:	0.5dBi
RF Power	8.5dBm

1.2 Test Facility

Site Description

Name of Firm : Dong Guan Anci Electronic Technology Co., Ltd.
Site Location : 1-2 Floor, Building A, No.11, Headquarters 2 Road,
Songshan, Lake Hi-tech Industrial Development Zone,
Dongguan City, Guangdong Pr., China.

2. GENERAL PRODUCT INFORMATION

2.1 Product Function and Intended Use

The submitted sample is wireless transceiver includes transmitter and receiver.

3. EN 62479 REQUIREMENT

3.1 General Description of Applied Standards

Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz).

3.2 Human exposure to the Electromagnetic fields

This International Standard provides simple conformity assessment methods for low-power electronic and electrical equipment to an exposure limit relevant to electromagnetic fields (EMF). If such equipment cannot be shown to comply with the applicable EMF exposure requirements using the methods included in this standard for EMF assessment, then other standards, including IEC 62311 or other (EMF) product standards, may be used for conformity assessment.

3.3 RF Exposure Evaluation

3.3.1 Limit:

According to EN 62479 clause 4.2 Low-power electronic and electrical equipment is deemed to comply with the provisions of this standard if it can be demonstrated using routes B, C or D that the available antenna power and/or the average total radiated power is less than or equal to the applicable low-power exclusion level P_{max} .

$P_{max} = 20 \text{ mW}$ (13 dBm) according to ICNIRP guidelines, since the EUT is General public used.

Remark:

B: The input power level to electrical or electronic components that are capable of radiating electromagnetic energy in the relevant frequency range is so low that the available antenna power and/or the average total radiated power cannot exceed the low-power exclusion level defined in EN 62479 clause 4.2

C: The available antenna power and/or the average total radiated power are limited by product standards for transmitters to levels below the low-power exclusion level defined in EN 62479 clause 4.2

D: Measurements or calculations show that the available antenna power and/or the average total radiated power are below the low-power exclusion level defined in EN 62479 clauses 4.2.

3.3.2 Test result

The EIRP of the EUT are below the max permitted sending level of 20 mW, and then the EUT is not need to conduct SAR measurement. more details

please refer to report: E01A23030814R00201. Please refer to the maximum EIRP.

4. APPENDIX PHOTOGRAPHS OF EUT.

Please refer to the report: E01A23030814E00201

-----The end of Report-----